

Company:

Account No.

Address:

..... Postcode:

Tel:

Fax:

Contact Name:

Email:

Requested Delivery Date:
(Lead time of 10 working days)

Order Reference:

Signature:

Page of

Quote

Order

FOLDING OPTIONS *(When viewed from outside)*

NB. Minimum sash width 550mm per pane, maximum sash width 1000mm per pane.

<p>.....</p> <p>Total number of leaves</p> <p>For Example: 3</p> <p><i>Total number of door leaves</i></p>	<p>.....</p> <p>Number of leaves folding left</p> <p>1</p> <p><i>Number of door leaves opening left</i></p>	<p>.....</p> <p>Number of leaves folding right</p> <p>2</p> <p><i>Number of door leaves opening right</i></p>	<p>Opening:</p> <p><input type="checkbox"/> In</p> <p><input type="checkbox"/> Out</p>
---	--	--	---

DIMENSIONS

Overall width:

.....





Maximum width: 6000mm

Overall height:

.....

Maximum height: 2400mm

EXTERNAL STYLING

<input type="checkbox"/> Pencil Round	
<input type="checkbox"/> Chamfered	
<input type="checkbox"/> Squared	
<input type="checkbox"/> Decorative	

**44mm Triple Glazed - Pencil Round only*

FRAME COLOUR

External:	Internal:
<input type="checkbox"/> White	<input type="checkbox"/> White
<input type="checkbox"/> Cream	<input type="checkbox"/> Cream
<input type="checkbox"/> Grey	<input type="checkbox"/> Grey
<input type="checkbox"/> Black	<input type="checkbox"/> Black

TRICKLE VENTS

Required Not required

HARDWARE

WarmCore

Silver

Black

Brushed Graphite

*Magnets are colour matched.
Locks/keeps are Anodised Silver.
Roller units are Black Anodised powder finish.
Brushed Graphite uses Anodised Black hinges.*

OPTIONAL LEVER/LEVER

Lever/Lever Handles	Magnets
<input type="checkbox"/> Silver	<input type="checkbox"/> Silver
<input type="checkbox"/> Black	<input type="checkbox"/> Black
<input type="checkbox"/> Brushed Graphite	<input type="checkbox"/> RAL 7016
	<input type="checkbox"/> White

Only fill in this section if Lever/Lever style handles are required on traffic doors.

SILL TYPE

Part M low threshold*

Part M low threshold ramp/cover*

Part M low threshold ramp/ramp*

Standard integrated 120mm sill *(Outward opening only)*


Frame + 150mm sill**

Frame only

**All Silver Anodised Aluminium.
**Part M low threshold is not compatible with 150mm sill.*

GLAZING OPTIONS

(All Toughened)

<input type="checkbox"/> Standard double glazed - 28mm (1.5 W/m ² K U-value*)	<input type="checkbox"/> Triple glazed - 44mm (1.0 W/m ² K U-value*)
<input type="checkbox"/> Celsius double glazed - 28mm (1.4 W/m ² K U-value*)	<input type="checkbox"/> Add Secured by Design Upgrade  Standard double glazed (Laminated) - 28mm (1.5 W/m ² K U-value*)
<input type="checkbox"/> Unglazed	<input type="checkbox"/> Laminated Unglazed

**Figures quoted are whole door U-values based on BFRC standard bi-fold door*

GLAZING BEAD

Squared/Squared - 28mm - 4 Sides

Squared/Chamfered - 28mm - Chamfered Verticals

Squared/Squared - 44mm - 4 Sides

Squared/Pencil Round - 28mm

SKETCH YOUR DESIGN HERE: *(When viewed from outside)*

Additional notes:

MAGNETS

Do you want the magnets fitted?

Yes No

ORDER GUIDELINES

MAXIMUM AND MINIMUM DOOR SIZES

STYLE	DOOR WIDTHS		DOOR HEIGHTS			
	MINIMUM	MAXIMUM	MINIMUM		MAXIMUM	
			FRAME / INTEG	PART M LT	FRAME / INTEG	PART M LT
220	1500	2126	2020	2000	2400	2400
330	1800	3138	2020	2000	2400	2400
321	1800	3138	2020	2000	2400	2400
440	3000	4150	2020	2000	2400	2400
431	2350	4150	2020	2000	2400	2400
422	3000	4150	2020	2000	2400	2400
550	2925	5162	2020	2000	2400	2400
541	2925	5162	2020	2000	2400	2400
532	2925	5162	2020	2000	2400	2400
660	4500	6000	2020	2000	2400	2400
651	3475	6000	2020	2000	2400	2400
642	4500	6000	2020	2000	2400	2400
633	3475	6000	2020	2000	2400	2400
770	4050	6000	2020	2000	2400	2400
761	4050	6000	2020	2000	2400	2400
752	4050	6000	2020	2000	2400	2400
743	4050	6000	2020	2000	2400	2400

NB: Heights noted do not include additional thermally broken sill.
Allow 26.5mm for this if it is required.

To order this door please sign below and email back to warmcoreorders@synseal.com or fax back to 01623 554050 as we now require all WarmCore orders to be signed back to us.

Signature:



Phone 01623 443200
Fax 01623 554050
Email warmcorequotes@synseal.com