

CELSIUS SOLID ROOF ENQUIRY FORM V3



Company:
 Account No.
 Address:
 Postcode:
 Tel:
 Fax:
 Mobile:
 Contact Name:
 Job Ref:

Required delivery date:

Use the grid below to draw a sketch of your roof design giving your dimensions in **millimetres** All sizes are **INTERNAL CILL**

HOUSE WALL

Show down pipe position with Please indicate all walls and box gutters if required

We will use 0.6kn/m² to calculate the snow loading on this roof, if you need this changed please let us know.

FASCIA/SOFFIT COLOUR

WHITE
 Cherrywood
 Golden Oak
 Mahogany

TILE COLOUR

BLACK
 Terracotta
 Dark Brown
 NEW Slate Grey

ROOF PITCH

Lean-to 12.5° **15°** 20° 25° 30°
 Duo 20° **25°** 30° 35°

GUTTER COLOUR

WHITE
 Brown
 Caramel
 Black

INTERNAL PELMET OPTIONS

150mm Ridge Pelmet
 300mm Eaves Pelmet
 Variables Eaves Pelmet.....mm*

warmcore
 FIXED ROOF LIGHT **NEW FIXED ROOF LIGHT**

630mm x 700mm 630mm x 1700mm
 630mm x 1200mm
 White Internal Finish Grey Internal Finish
 ** All Fixed Roof Windows have a **Black External Finish**

ROOF (VENT) WINDOW

550mm x 780mm 550mm x 1180mm
Standard for Roofs upto 3499mm wide *Large Vent Option*
 550mm x 980mm Opening Pole
Standard for Roofs over 3499mm wide *not included as standard*
 White Internal Finish Pine Internal Finish
 ** All Roof Windows have a **Grey External Finish**

* Please note the maximum depth of 1100mm is not available across all the conservatory styles. Pelmet depth will also alter on certain facets due to unequal pitches

Please note: If none of the boxes are ticked we will take as **STANDARD**
It is the installation companies sole responsibility to ensure the supporting structure offers adequate structural support for the new solid roof. It is also their responsibility to contact local Building Control to confirm if a Building Certificate is required.

Other notes/extras :

.....

.....

.....

Date:

Sign:

Print:

Email all enquiries to: consquotations@synseal.com
 Tel: 01623 443200
 Fax back to: 01623 443305
www.synseal.com